


Zeiss 700 Confocal Microscope

Location: HSC (Building 586) Room 56



The LSM 700 laser scanning confocal microscope is the seventh generation of confocal microscopes from Carl Zeiss. The LSM 700 system uses a Zeiss AXIO Observer Z1 inverted microscope with transmitted illumination (HAL 100) and a laser illumination source. The LSM 700 system features easy operation, excellent sensitivity, and a design that can handle complex tasks.

Main features of Zeiss 700 System:

- Two Photo Multipliers Tube (PMT1 and PMT2) detector unit enables simultaneous 12 bit (4096 intensity levels) acquisition of up to 4 fluorescent channels.
- Confocal scan head unit can provide high-resolution images up to 2048 x 2048 pixels in size.
- Fully automated Zeiss Observer Z1 inverted microscope.
- LED Epifluorescence and HAL100 Brightfield illumination lamps for rapid sample identification and focusing through the eyepiece.
- Filter wheel used for epifluorescence viewing of the sample is currently outfitted with DAPI , FITC (green), and Rhodamine (red) filter cube sets.
- Motorized XY stage with a variety of stage inserts available (slides, dishes, multiwall plates, etc..).
- Zeiss Zen Black multi-platform acquisition software.
- Measurements include: Z stack, Time lapse, Stitching/Tiling, XY positions, and Spectra unmixing

Suggested Applications:

- 3D Imaging.
- Multichannel fluorecence fixed slide imaging.
- Tiled mosaics.

Imaging lasers:

| Wavelength (nm) | Type | Power | Manufacturer |
|-----------------|-------|-------|-------------------------|
| 405 | diode | 5 mW | Lasos Lasertechnik GmbH |
| 488 | diode | 10 mW | Lasos Lasertechnik GmbH |
| 555 | diode | 10 mW | Lasos Lasertechnik GmbH |
| 639 | diode | 5 mW | Lasos Lasertechnik GmbH |

Objectives:

| Objective | Magnification | Immersion | Numerical Apperture | Correction Ring | Coverglass (mm) | Working Distance (mm) |
|----------------------|---------------|-----------|---------------------|-----------------|-----------------|-----------------------|
| EC Plan Neofluar M27 | 10X | Air | 0.3 | | 0.17 | 5.2 |
| Pan Apo M27 | 20X | Air | 0.8 | | 0.17 | 0.55 |
| LD C-Apo Korr M27 | 40X | Water | 1.1 | Corr | 0.14-0.19 | 0.62 |
| Pan Apo DIC M27 | 63X | Oil | 1.4 | | 0.17 | 0.19 |

Revision #7

Created 15 November 2023 18:30:11

Updated 20 March 2024 19:18:26